



- Doorplate: Grade A / Aluminium / Stainless Steel ; 8 mm
- Coaming: 75x50x7 Steel / Aluminium / Stainless Steel
- Cleats: Cast stainless steel: 1.4408 / ATSM CF8M equivalent to 1.4404 / AISI 316
- Mechanism: Stainless Steel 1.4404 / AISI 316L
- Seal: Seal 42.5x20.4 EPDM
- Wedge: Brass / POM
- Hinge: Stainless Steel or Aluminium with Orkot® bearing and Stainless Steel Axle

- Insulation : Rockwool Marineslab 55 or FireMaster Marine Plus Blanket :40mm / 70 kg m³

- Clear Opening: H x W
- Cut in plate: H + 75 x W + 75
- Outside dimensions: H + 150 x W + 150
- Handle length: L =375

	RM	10-2-2021	-
Revision Description	Name	Date	Rev
	Status: Released		
	Engineer: RM	8-2-2021	
American projection:	Description: WT Musketeer Door, 6 cleats, LH		
	Reference: Winel product catalog		
	Drawing number: 9546 XXXX		Rev. Sheet Size - 1 / 1 A2
	Dr. A.F. Philipsweg 55 9403 AD Assen The Netherlands info@winel.nl www.winel.nl +31 (0)592 366 060		
The drawing and design shown is our property and may not be used or disclosed for any third person without our specific written approval.			