



- Hatch cover: Grade A / Stainless Steel ; 8 mm
- Coaming: Raised FB Steel / Stainless Steel  
T = 8 - 10 - 12 - 15 mm
- Cleats: Cast stainless steel: 1.4408 / ATSM CF8M equivalent to 1.4404 / AISI 316
- Mechanism: Stainless Steel 1.4404 / AISI 316L
- Seal: Seal 42.5x20.4 EPDM 30 shore
- Wedge: Brass
- Hinge: Stainless Steel with Orkot® bearing and Stainless Steel Axle
  
- Insulation : Rockwool Marineslab 55 or FireMaster Marine Plus Blanket :40mm / 70 kg m<sup>3</sup>
- Clear Opening: D (min.Ø 600 -- max Ø850) // H (min. 160 )
- Cut in plate: D + 2\*T + 2 ( extended through the ship's deck )
- Outside dimensions: [ HS + 2 x T + 58 ] x [ W + 2 x T + 107 ]
- Handwheel diameter:L = Ø360, Casted Aluminium Standard
- Pressure: 0-5 mWc
- Locking pin: Inside ***Optional***
- T-key operation: Outside ***Optional***
- Anti piracy cap: Outside only ***Optional in combination with T-Key***
- O/C Marking: Outside only ***Optional***
- O/C Sensoring: ***Optional***

		RM	17-5-2023	-
Revision Description		Name	Date	Rev
		Status:	Released	
		Weight: 246,018 kg	Engineer: RM	13-10-2016
American projection:	Description: WT Musketeer Hatch   Raised Round Coaming   Springloaded			
Reference: Winel product catalog				
Drawing number: <b>9541.21XXX</b>			Rev.	Sheet
			-	1 / 1
			Size	A2
 <small>           info@winel.nl    Dr. A.F. Philipsweg 55            www.winel.nl    9403 AD Assen            +31 (0)592 366 060    The Netherlands         </small>				
The drawing and design shown is our property and may not be used or disclosed for any third person without our specific written approval.				