



- Hatch cover: Grade A / Stainless Steel ; 8 mm
- Coaming: Raised FB Steel / Stainless Steel
- T = 8 - 10 - 12 - 15 mm
- Cleats: Cast stainless steel: 1.4408 / ATSM CF8M equivalent to 1.4404 / AISI 316
- Mechanism: Stainless Steel 1.4404 / AISI 316L
- Seal: Seal 42.5x20.4 EPDM 30 shore
- Wedge: Brass
- Hinge: Stainless Steel with Orkot® bearing and Stainless Steel Axle
- Insulation : Rockwool Marineslab 55 or FireMaster Marine Plus Blanket :40mm / 70 kg m³
- Clear Opening: HxW min 800x800 max 1000x1000 // X (min. 160)
- Cut in plate: (H+T+2) x (W+T+2) (extended through the ship's deck)
- Outside dimensions: H + 332 x W +65
- Handwheel diameter:L = Ø360, Casted Aluminium Standard
- Pressure: 0-6 mWc
- Locking pin: Inside ***Optional***
- T-key operation: Outside ***Optional***
- Anti piracy cap: Outside only ***Optional in combination with T-Key***
- O/C Marking: Outside only ***Optional***
- O/C Sensoring: ***Optional***

-		RM	15-9-2023	-
Revision Description		Name	Date	Rev
Weight: 611,028 kg		Status:	Released	
		Engineer: RM	21-9-2016	
American projection:	Description: WT Musketeer Hatch - Spring Loaded - 6 cleats			
Reference: Winel product catalog				
Drawing number: 9541.31XXX			Rev.	Sheet
			-	1 / 1
			Size	A2
 <small> info@winel.nl Dr. A.F. Philipweg 55 www.winel.nl 9403 AD Assen +31 (0)592 366 060 The Netherlands </small>				
The drawing and design shown is our property and may not be used or disclosed for any third person without our specific written approval.				